

BiTLAN[®]F/UTP cat.5e outdoor

200 MHz

Data transmission cable, screened, suitable for external applications



BITNER BiTLAN F/UTP 4x2x24AWG(0,5) cat. 5e outdoor 200MHz



Technical data:

Thermal parameters:

Temperature range:

operating temperature: -30 °C to 80 °C
min. installation temp: -10 °C


Electrical parameters:

Conductor diameter: 0,5 ± 0,015 mm
Insulated core diameter: 0,92 ± 0,03 mm
DC loop resistance at 20 °C (max):
190 Ω/km
Insulation resistance (min): 5 GΩ x km
Resistance unbalance within a pair: ≤ 2 %
Mutual capacitance at 1 kHz: 50 ± 5nF/km
Capacitance unbalance pair to ground at 1 kHz (max): 1600 pF/km
Nominal voltage: 150 V
Test voltage at 1 min.:
AC 50 Hz: 700 V
DC: 1000 V
Characteristic impedance at 100 MHz:
100 ± 5 Ω
NVP value: 67 %
Return loss dB (min):
f = 4 + 10 MHz: 20 + 5 x log₁₀(f)
f = 10 + 20 MHz: 25
f = 20 + 200 MHz: 25 - 7 x log₁₀(f/20)
Coupling attenuation within the range of 30 + 100 MHz (min.): 50 dB
Transfer impedance at 10 MHz (max):
100 mΩ/m

Mechanical parameters:

Bending radius:

during operation: ≥ 6 x Ø
during installation: ≥ 8 x Ø



Design:

Conductors: solid round copper conductors
Insulation: special polyolefin compound
Core identification: wh/bu-bu, wh/or-or, wh/gn-gn, wh/bn-bn
Core arrangement: cores twisted in pairs, pairs twisted together
Screen: Al/Pet screen with tinned copper drain wire
Outer sheath: polyethylene PE
Outer sheath colour: black

Marking: BITNER BiTLAN F/UTP 4x2x24AWG(0,5) cat.5e outdoor 200MHz
EN 50173-1 ISO/IEC 11801 ANSI/TIA 568-C.2 ID no. CE RoHS
www.bitner.com.pl meters

Application:

BiTLAN F/UTP cat.5e outdoor 200MHz outdoor cables are applicable to computer networks with operating frequency band up to 200MHz. Suitable for transmission of data, audio and video signals, with bitrate up to 1Gb/s. Dedicated for fixed installations within outdoor structured cabling systems as per EN 50173-1, ISO/IEC 11801, ANSI/TIA 568-C.2 standards, as well as within industrial networks exposed to external electromagnetic interferences. UV resistant outer sheath enables external application. Cables classified according to **EN 50575 (CPR)**.

Packaging:

plywood reel
500mplywood reel/
drum
1000m

Cat. no.	Construction	Cu wire	Outer diameter* [mm]	CPR classification EN 50575	Cable weight [kg]	Bandwidth [MHz]
T10051	F/UTP cat.5e outdoor	24AWG(0,5)	6,8	Fca	40	200

*Outer diameter tolerance: +/-5%

Cable Factory BITNER reserves the right to modify the specifications without prior notice

BiTLAN[®] F/UTP cat.5e outdoor

200 MHz

Data transmission cable, screened, suitable for external applications

Requirements of teletransmission data:

Frequency MHz	1	4	10	16	20	30	45	60	80	100	120	130	155	175	200
Attenuation \leq dB/100m	2,1	4,0	6,3	8,0	9,0	11,2	13,9	16,2	18,9	21,3	23,6	24,7	27,2	29,2	31,5
NEXT \geq dB	65,3	56,3	50,3	47,2	45,8	43,1	40,5	38,6	36,7	35,3	34,1	33,6	32,4	31,6	30,8
PS NEXT \geq dB	62,3	53,3	47,3	44,2	42,8	40,1	37,5	35,6	33,8	32,3	31,1	30,6	29,5	28,6	27,8
ELFEXT \geq dB/100m	63,8	51,8	43,8	39,7	37,8	34,3	30,7	28,2	25,7	23,8	22,2	21,5	20,0	19,0	17,8
PS ELFEXT \geq dB/100m	60,8	48,8	40,8	36,7	34,8	31,3	27,7	25,2	22,7	20,8	19,2	18,5	17,0	16,0	14,8
RL \geq dB	20,0	23,0	25,0	25,0	25,0	23,8	22,5	21,7	20,8	20,1	19,5	19,3	18,8	18,4	18,0

Transmission parameters graphs - examples of measurement results

