

BiT L2 BUS LSOH

O2YS(St)CH, Data transmission, halogen-free cables for Profibus network



industrial application



internal application



EN 60332-1-2



data transmission



halogen-free
EN 60754



low smoke emission
EN 61034



EMC

Technical data:

Thermal parameters:

Temperature range:

operating temperature: -40 °C to 80 °C
min. installation temp: -5 °C

Electrical parameters:

Wave impedance: 150 Ω ±10%

Conductor loop resistance (max.): 115 Ω/km

Screen resistance (max.): 9,7 Ω/km

Insulation resistance: 1 GΩ x km

Capacitance: 30 nF/km

Test voltage: 1500 V

Wave attenuation at a frequency of:

1 MHz = 1,2 dB/100 m

4 MHz = 2,2 dB/100 m

10 MHz = 3,2 dB/100 m

16 MHz = 4,2 dB/100 m

Mechanical parameters:

Min. bending radius: 8 x Ø

Design:

Conductors:

solid copper conductors 1 x 2 x 0,64 mm

Insulation:

made of foamed polyethylene with a thin external layer of solid polyethylene

Core identification:

red, green

Core arrangement:

cores twisted together with two fillers

Screens:

aluminium backed polyester tape and tinned copper wire braid

Outer sheath:

special halogen-free, self-extinguishing and flame retardant (as per EN 60332-1-2); colour: purple

Application:

L2-BUS LSOH cables are intended for connecting components (standard 486) and transmission of analogue and digital signals. Paired construction ensures good symmetry with respect to earth, while the double screen protects against interferences from external electromagnetic fields, what guarantees very good transmission quality. Cables may be used in dry and damp rooms, and are suitable for fixed installations. Cables classified according to **EN 50575 (CPR)**.

Cat. no.	n x 2 x mm	Outer diameter* [mm]	Approximate cable weight [kg/km]
EB0200	1x2x0,64	7,6	59

*Outer diameter tolerance: +/-5%

Cable Factory BITNER reserves the right to modify the specifications without prior notice