

BiTsound® LP0216 DMX 512/1990 Dual Data Cable 110 Ohm OFC

Flexible, two pair cable for transmitting digital signals

DMX CABLES



Technical data:

Operating temperature:

Fixed installation: -30°C to 70°C

Flexible connections: -5°C to 70°C

Min. installation temperature: -5°C

Capacitance (at 1kHz):

conductor/conductor: ≤ 60nF/km

conductor/screen: ≤ 115nF/km

Impedance: 110Ω±10

Min. insulation resistance: 1GΩxkm

Min. bending radius: 5xØ (Ø - cable diameter)

Construction:

Conductors: tinned copper, multi-stranded conductors (8x0,20)

Insulation: special PE

Core identification:

1st pair: white, red

2nd pair: green, blue

Core arrangement: pairs twisted together with textile fillers

Screen: aluminium backed polyester tape with tinned copper drain wire underneath and tinned copper wire braid with coverage min. 85%

Outer sheath: special PVC, self-extinguishing and flame retardant acc. to EN 60332-1

Outer sheath colour: black, matt

Application:

BiTsound®LP0216 DMX 512/1990 Dual Data Cable 110 Ohm OFC is professional, flexible, two pair cable designed for transmitting digital signals e.g. in lighting or stage motion systems. It is double screened with tinned copper wire braid and AL/PET tape with additional drain wire what ensures very good protection against external interferences and improves the quality of transmitted signals. The cable is dedicated to professional and studio applications. Matt outer sheath eliminates the light reflection effect.

BiTsound®LP0216 DMX 512/1990 Dual Data Cable 110 Ohm OFC is classified in accordance with **EN 50575 (CPR)**.

Cable properties:

- high impact strength and flexibility at both room and low temperatures
- high flexibility
- matt outer sheath eliminating the light reflection effect

Cat. no.	Colour	nxmm ²	Nominal O.D. [mm]	Nominal weight [kg/km]	Max. screen resistance DC at 20°C [Ω/km]	Max. resistance of power conductors DC at 20°C [Ω/km]
LP0216	black	2x(2x0,25)	7,8	80	15,5	79

Cable Factory BITNER reserves the right to modify the specifications without prior notice.
Note: On customer's request other cross sections or number of cores can be produced.

