

BITflex[®](N)TMCGCWOEU

RoHS 2015/863/EU


CPR

CPR 305/2011



24 months warranty

Medium voltage, screened single core cable based on DIN VDE 0250-813



mining applications



industrial application



EN 60332-1-2



high flexibility



oxygen index



UV resistance

oil resistant
EN 60811-404

Technical data:

Thermal parameters:

Ambient temperature:

fixed installation: -40 °C to 80 °C

flexible operation: -25 °C to 80 °C

Max. permissible conductor temp.: 90 °C**Max. short-circuit temp. at conductor:** 200 °C**De-rating factors:** acc. to DIN VDE 0298-4

Mechanical parameters:

Max. tensile load per conductor: 15 N/mm²

Bending radius:

- fixed installation: $\geq 6 \times \text{outer-}\varnothing$ - free moving: $\geq 8 \times \text{outer-}\varnothing$

Design:

Main cores

Conductor: tinned copper wires, finely stranded, class 5 acc. to DIN EN / IEC 60228

Insulation:

- inner semi-conductive stress control layer
- EPR compound with improved electrical and mechanical characteristics based on DIN VDE 0207-20
- outer semi-conductive insulation shield layer

Screen:

concentric ground conductor: spinning with tinned copper wire strands acc. to DIN VDE 0250-1, covering approx. 85 %

Outer sheath:

heavy duty rubber compound, type 5GM5 acc. to DIN VDE 0207-21, flame retardant acc. to EN 60332-1-2, oil resistance acc. to EN 60811-404, ozone, UV and moisture resistant, colour: red, inkjet marking

Application:

Flexible high voltage cable used in short lengths, e.g. as a connection in switch-gear or transformer houses where small bending radius is requested. Cable are also used in slow moving Offshore-Power-Systems: energy chains or reeling operation or power supply for large electrical applications and drives via cable carrier systems.

Approvals:

UL Classified

Chemical parameters:

Resistance to oil:

DIN EN / IEC 60811-404

Behaviour in case of fire:

DIN EN / IEC 60332-1-2

Weather resistance:

unrestricted use indoors, outdoors, resistance to ozone, UV and moisture

Rated voltage U_r/U [kV]	3.6/6	6/10	8.7/15	12/20	14/25	18/30
Maximum permissible operating voltage $U_{0,max}$ in AC systems [kV]:	4.2/7.2	6.9/12	10.4/18	13.9/24	17.3/30	20.8/36
Maximum permissible operating voltage $U_{0,max}$ in DC systems [kV]:	5.4/10.8	9/18	13.5/27	18/36	22.5/45	27/54
AC. test voltage acc. to DIN VDE 0250-813 [kV]:	11	17	24	29	36	43

Cable Factory BITNER reserves the right to modify specifications without prior notification.

Note: on customer's request other cross sections or number of cores can be produced

BiTflex[®](N)TMCGCWOEU

Medium voltage, screened single core cable based on DIN VDE 0250-813

BiTflex[®](N)TMCGCWOEU 6/10 kV

n x mm ²	Maximum conductor resistance	Nominal diameter over insulation	Outer diameter min.-max. [mm]	Approximate cable weight [kg/km]	Current carrying capacity ¹⁾
1x25/16	0.795	13,0	22-25	790	135
1x35/16	0.565	14,5	23-26	930	169
1x50/16	0.393	16,0	25-28	1130	207
1x70/16	0.277	18,0	27-30	1380	268
1x95/16	0.210	19,0	29-32	1640	328
1x120/16	0.164	21,0	31-34	1990	383
1x150/25	0.132	23,0	33-36	2320	444
1x185/25	0.108	25,0	35-38	2680	510
1x240/25	0.0817	27,0	38-41	3300	607

BiTflex[®](N)TMCGCWOEU 12/20 kV

n x mm ²	Maximum conductor resistance	Nominal diameter over insulation	Outer diameter min.-max. [mm]	Approximate cable weight [kg/km]	Current carrying capacity ¹⁾
1x25/16	0.795	17,0	26-29	1010	135
1x35/16	0.565	18,0	27-30	1160	169
1x50/16	0.393	19,0	28-31	1350	207
1x70/16	0.277	21,0	31-34	1670	268
1x95/16	0.210	23,0	33-36	1940	328
1x120/16	0.164	24,0	35-38	2230	383
1x150/25	0.132	26,0	37-40	2660	444
1x185/25	0.108	28,0	39-42	3040	510
1x240/25	0.0817	30,0	41-44	3580	607

¹⁾ acc. to IEC 60364-5-52, conductor temperature: 90 °C/Reference ambient temperature: 30 °C, free in air, based on installation method F, three loaded conductors trefoil, values for further installation methods on request

Cable Factory BITNER reserves the right to modify specifications without prior notification.
Note: on customer's request other cross sections or number of cores can be produced