


BiTcrane[®] (N)SHTOEU-J FO



Crane cables

Low voltage, reeling cable based on DIN VDE 0250-814



Technical data:

Thermal parameters:

Ambient temperature:
 fixed installation: -40 °C to 80 °C
 reeling operation: -30 °C to 80 °C
Max. permissible conductor temp.: 90 °C
Max. short-circuit temp. at conductor: 250 °C

Mechanical parameters:

Tensile load static/dynamic: 15 / 30 N/mm²
Torsional stresses: ± 25 °/m
Bending radius acc. to DIN VDE 0298-3:
 - fixed installation: ≥ 4 x cable - Ø
 - reeling application: ≥ 6 x cable - Ø
 - on deflection pulleys: ≥ 7.5 x cable - Ø
 - min. distance with S-type directional changes:
 20 x cable - Ø
Reeling speed: ≤ 180 m/min

Design:

Main cores:
Conductors: plain copper wires, finely stranded, acc. to IEC 60228 class 5
Insulation: HEPR compound acc. to IEC 60502-1, core colours: acc. to DIN VDE 0293-308

Ground conductor:
Conductor: plain copper wires, finely stranded, acc. to IEC 60228 class 5
Insulation: HEPR compound acc. to IEC 60502-1, core colours: green-yellow

Optical fiber element: 12 / 2x12 fibers in G62.5/125, G50/125 or E9/125 various fiber combinations on request
Inner sheath: heavy duty rubber compound, quality 5GM5 acc. to DIN VDE 0207-21, filling the interstices
Reinforcement: braid made of synthetic threads, in a vulcanized bond between inner and outer sheath
Outer sheath: heavy duty rubber compound, quality 5GM5 acc. to DIN VDE 0207-21, colour: black, inkjet marking

optional version with a cradle separator (K) available on request

Application:

Heavy duty rubber reeling cable for power supply including optional optical data transfer. For applications with high mechanical stress, especially for simultaneous tensile and torsional stress. Suitable for all types of mobile equipment such as stackers/reclaimers, on container handling equipment of any kind in ports or stockyard areas with motor-driven mono spiral / cylindrical reels or spring-operated reels.

Chemical parameters:

Resistance to oil: DIN EN / IEC 60811-404
 Behaviour in case of fire: DIN EN / IEC 60332-1-2
 Weather resistance: unrestricted use indoors, outdoors, resistance to ozone, UV and moisture

Electrical parameters:

| | |
|---|---------------------------------|
| Rated voltage U_0/U [kV] | 0.6/1 kV |
| Maximum permissible operating voltage $U_{0,max}$ in AC systems [kV]: | 0.7/1.2 kV |
| Maximum permissible operating voltage $U_{0,max}$ in DC systems [kV]: | 0.9/1.8 kV |
| AC test voltage: | 3.5 kV |
| Current-carrying capacities in amperes: | acc. to DIN VDE 0298-4 table 15 |
| De-rating factors (thermal/reeling): | acc. to DIN VDE 0298-4 |

Bitcrane[®] (N)SHTOEU-J FO

Low voltage, reeling cable based on DIN VDE 0250-814

Crane cables

Protective conductor cross-section split into two parts, optical fiber element in the third interstice

| n x mm ² | Outer diameter min. – max. [mm] | Approximate cable weight [kg/km] |
|----------------------|---------------------------------------|--|
| 3x16+2x16/2+12FO | 36-39 | 1940 |
| 3x25+2x16/2+12FO | 36-39 | 2130 |
| 3x35+2x16/2+12FO | 37-40 | 2380 |
| 3x50+2x25/2+12FO | 42-45 | 3200 |
| 3x70+2x35/2+12FO | 47-50 | 4280 |
| 3x95+2x50/2+12FO | 53-56 | 5500 |
| 3x120+2x70/2+12FO | 59-62 | 6870 |
| 3x150+2x70/2+12FO | 59-62 | 7560 |
| 3x185+2x95/2+12FO | 69-72 | 9790 |
| 3x240+2x120/2+12FO | 78-81 | 12660 |
| 3x300+2x150/2+12FO | 82-85 | 15080 |
| | | |
| 3x25+2x16/2+2x12FO | 44-47 | 2890 |
| 3x35+2x16/2+2x12FO | 45-48 | 3150 |
| 3x50+2x25/2+2x12FO | 42-45 | 3200 |
| 3x70+2x35/2+2x12FO | 47-50 | 4260 |
| 3x95+2x50/2+2x12FO | 53-56 | 5480 |
| 3x120+2x70/2+2x12FO | 59-62 | 6850 |
| 3x150+2x70/2+2x12FO | 59-62 | 7540 |
| 3x185+2x95/2+2x12FO | 69-72 | 9770 |
| 3x240+2x120/2+2x12FO | 78-81 | 12640 |
| 3x300+2x150/2+2x12FO | 82-85 | 15060 |

Regulations of the individual fibre types:

| Fiber optic type | Standard | Colour code |
|-----------------------------------|---------------|----------------------------|
| Single-mode optical fiber E9/125 | ITU-T G.652 D | acc. to ANSI/TIA/EIA 598-A |
| Multimode fiber G50/125 (OM2-OM4) | ITU-T G.651 | |
| Multimode fiber G62,5/125 | | |

Typical attenuation values:

| Fiber optic type | Description | Value (max.) | Unit |
|----------------------------------|------------------------|--------------|-------|
| Single-mode optical fiber E9/125 | attenuation at 1310 nm | 0,5 | dB/km |
| Single-mode optical fiber E9/125 | attenuation at 1550 nm | 0,3 | dB/km |
| Multimode fiber G50/125 | attenuation at 850 nm | 3,0 | dB/km |
| Multimode fiber G50/125 | attenuation at 1300 nm | 1,0 | dB/km |
| Multimode fiber G62,5/125 | attenuation at 850 nm | 3,5 | dB/km |
| Multimode fiber G62,5/125 | attenuation at 1300 nm | 1,5 | dB/km |

Cable Factory BITNER reserves the right to modify the specifications without prior notice
 Note: on customer's request other cross sections or number of cores can be produced